

Globe LED Lighting: Light Panels

Globe LED Lighting's attractive flat panel lighting system

Ideal for office buildings, retailers, institutions and hospitals



PRODUCT FEATURES

- Designed to fit into standard T-Bar ceiling systems or can be surface mounted
- Seamless constructed electroplated frame with rounded corners for maximum strength and safety
- Driver contained in protective junction box affixed to rear of light panel for stability
- Designed for 100-277V or 277-347V 50-60 Hz input, Power Factor 0.9, Total Harmonic Distortion <18%
- Lighting efficiency of 101 lumens per watt, 4040 lumens for 40 watt 2 foot x 2 foot or 1 foot x four lights
- Lighting efficiency of 101 lumens per watt, 7575 lumens for 75 watt 2 foot x 4 foot lights
- Wide temperature operating range -25° to +40°C
- Thin 11 mm deep profile, smooth even illumination, easy to connect wiring
- UL and cUL registered LED, DLC (DesignLights Consortium) approved
- Projected product life and product warranty of 5 years

PRODUCT BENEFITS

- Highly energy efficient alternative to fluorescent and other ceiling mounted lighting
- Exceptional lighting quality and an attractive addition to any room décor
- Maintenance free during projected 5 year lifespan
- Qualifies for IESO saveONenergy and other utility conservation incentive programs

OPTIONS

- Sizes: 1'x4', 2'x2' and 2'x4'
- Current: 100-277V or 277-347V
- Light Colour: 3000, 4000 or 5000K
- Frame Colour: White or Silver

LIGHT PANELS - TWO FOOT x TWO FOOT

GLL-LP-2x2-110-277V-4K-D-W
Light Panel, 2FTx2FT, 40W, 4040L, 4000K, AC110-277V/DC24V Driver, Dimmable, White Frame
cUL & DLC Approved

GLL-LP-2x2-110-277V-5K-D-W
Light Panel, 2FTx2FT, 40W, 4040L, 5000K, AC110-277V/DC24V Driver, Dimmable, White Frame,
cUL & DLC Approved

GLL-LP-2x2-277-347V-4K-D-W

Light Panel 2FTx2FT, 40W, 4040L, 4000K, AC277-347V-DC24V Driver, Dimmable, White Frame

cUL & DLC Approved

GLL-LP-2x2-277-347V-5K-D-W

Light Panel 2FTx2FT, 40W, 4040L, 5000K, AC277-347V-DC24V Driver, Dimmable, White Frame

cUL & DLC Approved

LIGHT PANELS - ONE FOOT x FOUR FOOT

GLL-LP-1x4-110-277V-4K-D-W

Light Panel, 1FTx4FT, 40W, 4040L, 4000K, AC110-277V/DC24V Driver, Dimmable, White Frame

cUL & DLC Approved

GLL-LP-1x4-110-277V-5K-D-W

Light Panel, 1FTx4FT, 40W, 4040L, 5000K, AC110-277V/DC24V Driver, Dimmable, White Frame,

cUL & DLC Approved

GLL-LP-1x4-277-347V-4K-D-W

Light Panel 1FTx4FT, 40W, 4040L, 4000K, AC277-347V-DC24V Driver, Dimmable, White Frame

cUL & DLC Approved

GLL-LP-1x4-277-347V-5K-D-W

Light Panel 1FTx4FT, 40W, 4040L, 5000K, AC277-347V-DC24V Driver, Dimmable, White Frame

cUL & DLC Approved

LIGHT PANELS - TWO FOOT x FOUR FOOT

GLL-LP-2x4-110-277V-4K-D-W

Light Panel, 2FTx4FT, 75W, 7575L, 4000K, AC110-277V/DC24V Driver, Dimmable, White Frame

cUL & DLC Approved

GLL-LP-2x4-110-277V-5K-D-W

Light Panel, 2FTx4FT, 75W, 7575L, 5000K, AC110-277V/DC24V Driver, Dimmable, White Frame,

cUL & DLC Approved

GLL-LP-2x4-277-347V-4K-D-W

Light Panel 2FTx4FT, 75W, 7575L, 4000K, AC277-347V-DC24V Driver, Dimmable, White Frame
--

cUL & DLC Approved

GLL-LP-2x4-277-347V-5K-D-W

Light Panel 2FTx4FT, 75W, 7575L, 5000K, AC277-347V-DC24V Driver, Dimmable, White Frame
--

cUL & DLC Approved
